

MATERIAL SAFETY DATA SHEET

Date –Issued:02/06/2006 Date –Revised:01/08/2009 MSDS Ref.No:PSMSD-483-4

Page: 1 of 3

1. PRODUCT AND COMPANY IDETIFICATION

PRODUCT NAME: Sticky MoS2 Grease FXM-3

GENERAL USE: Lubricant for bearings, gears, rails, etc.,...

PRODUCT FORMULATION NAME: Lubricating base oil, Fumed silica, MoS2 performance additives.

MANUFACTURER

LONG LUB-TEK (TAIWAN) CORPORATION

330-12 Sec.1 Zhong Zheng Rd. Sanxia Dist., New Taipei City TAIWAN.Phone No.: 886-2-26742566Fax No.: 886-2-26742730

2. TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	sticky black semi-solid
Odor	mild
Specific gravity	
Flash point(COC) °C min	235
Dropping point(COC) °C min.	none

3. FIRE AND EXPLOSION HAZARD DATA

Flash point(COC) ℃ : 235°C
Flammable Class: Flammable
Extinguishing media: Carbon Dioxide, Foam, Dry chemical, Water
Special Fire-fighting Procedures: Water may be used to cool containers exposed to heat.

Unusual Fire Hazards: Treat like petroleum fire.

----continued----

4. HEALTH HAZARD DATA			
]	DANGER:	IRRITATING TO THE EYES	
Eye Irritation	(Rabbits)	Corrosive to the Eye	
Skin Irritation	(Rabbits)	Mild Primary Skin Irritant	
DOT Skin Corrosion	(Rabbits)	Non-Corrosive: Mild Primary Skin Irritant	
Acute Dermal Toxic	ity (Rabbits)	LD50>20.000mg/Kg	
Acute Inhalation	(Rats)	LC50>18mg/l	
Acute Oral Toxicity	(Rats)	LD50>5.000mg/Kg	
Skin Sensitivity	(Guinea Pig	s) Buehler – Minimal contact sensitizer	

5. EMERGENCY AND FIRST AID PROCEDURE

- **EYES:** Wash eyes with clean flowing water for two or three minutes. Remove any contact lenses and continue flushing for 15 minutes. If irritation occurs or persists, get medical attention.
- **SKIN:** Remove contaminated clothing including shoes and wash affected area with soap and water. Wash contaminated clothing and shoes before reuse.
- **INGESTION:** Induce vomiting, wash out mouth with water and keep at rest. Seek immediate medical attention.

6. SPILL OR LEAK PROCEDURE

Small Amounts: Shovel up and place in closed containers for disposal.Large Amounts: Dike to container and place into drums for use or disposal.

7. DISPOSAL METHODS

Not a hazardous waste under RCRA (40CFR 261). Dispose of in the manner prescribed in Federal, State and Local regulations.

8. SPECIAL PROTECTION INFORMATION

Eye Protection:Wear safety goggles.Protective Gloves:Wear oil impervious gloves.

----continued----

9. SPECIAL PRECAUTIONS DO NOT ALLOW EYE CONTACT AVOID SKIN CONTACT DO NOT INGEST KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE EYEWASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE EASILY ACCESS

EYEWASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE EASILY ACCESIBLE WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING

10. REGULATORY INFORMATION

DOT Class:	Not regulated	
DOT Number; UN #:	Not Applicable	
RCRA Status:	Material is not a hazardous waste under RCRA (40 CFR 261)	

NTP, IARC and OSHA: Not listed as a carcinogen.

U.S. TSCA, EEC EINECS, Japan MITI, Canada DSL, Australia AICS:

All components are listed or in compliance with current regulations.

SARA Title III Section 313 Supplier Notification:

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.