

# MATERIAL SAFETY DATA SHEET

**Date – Issued:** 06/06/2008 **MSDS Ref.No:** PSMSD-300-1

**Date –Revised:04**/24/2010 **Page:** 1 of 4

## 1. PRODUCT AND COMPANY IDETIFICATION

**Product Name:** Fuel Additive GT300

**MANUFACTURER** 

LONG LUB-TEK CORPORATION

330-12 Sec.1 Zhong Zheng Rd. Sanxia Dist., New Taipei City TAIWAN.

Phone No.: 886-2-26742566 Fax No.: 886-2-26742730

## 2. PRODUCT FORMULATION NAME

**General Use:** Gasoline fuel additive.

**Ingredient:** 

Ingredient CAS # Weight Percent
Aliphatic hydrocarbon 64742-47-8 35-45
Organic solvent 67-63-0 40-50
Performance additive Mixture 12-18

## 3. HEALTH HAZARD/TOXICOLOGICAL INFORMATION

Eye Contact: Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin Contact:** This product has low skin irritation potential. There is no dermal toxicity hazard.

Inhalation (Breathing): No inhalation hazard expected with water vapor.

**Ingestion (Swallowing):** Based on ingredients, LD50 (rat) is estimated to be well over 50 g/kg.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC or OSHA, nor have any of its components.

----continued----

#### 4. FIRE AND EXPLOSION HAZARD DATA

Flash Point:  $40^{\circ}$ C.

Flammable Class: Flammable

Extinguishing media: Carbon Dioxide, Foam, Dry chemical

Special Fire-fighting Procedures: Water may be used to cool containers exposed

to heat.

**Unusual Fire Hazards:** Treat like petroleum fire.

### 5. HAZARDOUS INGREDIENTS

This product contains no reportable hazardous components under 29 CFR 1910.1200. There are no OSHA or ACGIH threshold limit values for the product or any of its ingredients.

All components are listed on the TSCA inventory.

#### 6. HEALTH HAZARD DATA

Eye Irritation (Rabbits) Corrosive to the Eye

Skin Irritation (Rabbits) Non Primary Skin Irritant

DOT Skin Corrosion (Rabbits) Non-Corrosive: Non Primary Skin Irritant

Acute Dermal Toxicity (Rabbits) LD50>20.000mg/Kg

Acute Inhalation (Rats) LC50>18mg/l

Acute Oral Toxicity (Rats) LD50>5.000mg/Kg

Skin Sensitivity (Guinea Pigs) Buehler – Minimal contact sensitizer

#### 7. EMERGENCY AND FIRST AID PROCEDURE

**EYES:** Wash eyes with clean flowing water for two or three minutes. Remove any contact lenses and continue flushing for 15 minutes. If irritation occurs or persists, get medical attention.

**SKIN:** Remove contaminated clothing including shoes and wash affected area with soap and water. Wash contaminated clothing and shoes before reuse.

**INGESTION:** Induce vomiting, wash out mouth with water and keep at rest. Seek immediate medical attention.

----continued----

#### 8. SPILL OR LEAK PROCEDURE

Small Amounts: Add oil adsorbent, shovel up and place in closed containers for

disposal.

**Large Amounts:** Dike to container and pump into drums for use or disposal.

#### 9. DISPOSAL METHODS

Not a hazardous waste under RCRA (40CFR 261). Dispose of in the manner prescribed in Federal, State and Local regulations.

## 10.TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

**Appearance: Clear liquid** 

Color: Amber Odor: Mild

**Specific Gravity:** 0.790

Flash Point: 40°C

**Decompose Temperature:** >300°C

## 11.SPECIAL PROTECTION INFORMATION

**Eye Protection:** Wear safety goggles.

**Protective Gloves:** Wear oil impervious gloves.

**Respiratory:** If misting occurs, use NIOSH approved respirator for oil mist

Provide general, mechanical ventilation.

Keep away from children, infants, and pets.

#### 12.REACTIVITY DATA

**Stability: Stable** 

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition.

**Incompatibilities: Strong oxidizing agents.** 

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

----continued----

#### 13.HANDLIND AND STORAGE

**Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

**Storage:** Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class II Liquid.

## 14. TRANSPORTATION INFORMATION

DOT Surface Shipping Description: Excepted from Hazmat (49CFR 173.150 (F)) in non-bulk packagings.

Bulk Packagings: NA1993, Combustible Liquid, n.o.s. (contains Petroleum Distillates), PG II

IMDG Shipping Description: UN1268, Petroleum Distillates, n.o.s. 2, PG II

#### 15.OTHER INFORMATION

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

**Revision Date** 24.04.2009