

MATERIAL SAFETY DATA SHEET

Date –Issued:05/06/2006 **MSDS Ref.No:**PSMSD-790-2

Date –Revised:06/28/2010 **Page:** 1 of 3

1. PRODUCT AND COMPANY IDETIFICATION

PRODUCT NAME: Tungsten Carbide Grinding Fluid #790

GENERAL USE: Water soluble grinding fluid for Tungsten Carbide parts .

PRODUCT FORMULATION NAME: Organic acid salt corrosion inhibitor,

Biocide, anti-foam agent, water

MANUFACTURER

LONG LUB-TEK CORPORATION

330-12 Sec.1 Zhong Zheng Rd. Sanxia Dist., New Taipei City TAIWAN.

Phone No.: 886-2-26742566 Fax No.: 886-2-26742730

2. TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

| Appearance | Amber liquid |
|---------------------------|--------------|
| Odor | mild |
| Specific gravity | 1.02 |
| Flash point(COC) °C min | None |
| PH (1% dilution in water) | 9.5 |

3. FIRE AND EXPLOSION HAZARD DATA

Flash Point: No flash via TCC.

Flammable Limits: Product is not flammable.

Extinguishing Media: Does not apply. Special Procedures: Does not apply.

Unusual Hazards: Sealed container can build up pressure when exposed to

high heat. Cool containers with water.

Page: 2 of 3

4. HEALTH HAZARD DATA

DANGER: CORROSIVE TO THE EYES WARNING: IRRITATING TO THE SKIN

Eye Irritation (Rabbits) Corrosive to the Eye

Skin Irritation (Rabbits) Moderate Primary Skin Irritant

DOT Skin Corrosion (Rabbits) Non-Corrosive: Moderate Primary Skin Irritant

Acute Dermal Toxicity (Rabbits) LD50>20.000mg/Kg

Acute Inhalation (Rats) LC50>18mg/l

Acute Oral Toxicity (Rats) LD50>5.000mg/Kg

Skin Sensitivity (Guinea Pigs) Buehler – Minimal contact sensitizer

5. EMERGENCY AND FIRST AID PROCEDURE

EYES: Wash eyes with clean flowing water for two or three minutes. Remove any contact lenses and continue flushing for 15 minutes. If irritation occurs or persists, get medical attention.

SKIN: Remove contaminated clothing including shoes and immediately wash affected area with plenty of soap and water. Seek medical attention. Wash contaminated clothing and shoes before reuse.

INGESTION: Induce vomiting, wash out mouth with water and keep at rest. Seek immediate medical attention.

6. SPILL OR LEAK PROCEDURE

Small Amounts: Flush with large volume of water.

Large Amounts: Dike to container and pump into drums for use or disposal.

7. DISPOSAL METHODS

Not a hazardous waste under RCRA (40CFR 261). Dispose of in the manner prescribed in Federal, State and Local regulations.

8. SPECIAL PROTECTION INFORMATION

Eye Protection: Wear safety goggles.

Protective Gloves: Wear oil impervious gloves.

Respiratory: If misting occurs, use NIOSH approved respirator for oil mist

Provide general, mechanical ventilation.

----continued----

Page: 3 of 3

9. SPECIAL PRECAUTIONS

DO NOT ALLOW EYE CONTACT AVOID SKIN CONTACT DO NOT INGEST

KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE EYEWASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE EASILY ACCESIBLE WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING

10. REGULATORY INFORMATION

DOT Class:Not regulated **DOT Number; UN #:**Not Applicable

RCRA Status: Material is not a hazardous waste under RCRA

(40 CFR 261)

NTP, IARC and OSHA: Not listed as a carcinogen.

U.S. TSCA, EEC EINECS, Japan MITI, Canada DSL, Australia AICS:

All components are listed or in compliance with current regulations.

SARA Title III Section 313 Supplier Notification:

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.